


SWING BOLTS

STEEL: 1144, 115,000 PSI MIN. TENSILE STRENGTH, 100,000 PSI MIN. YIELD STRENGTH, BLACK OXIDE FINISH



Shoulder-type Eye Bolt that can be used as a stationary hinge point. Reamed hole for smooth bearing.



INCH

| PART NO. | A       | B DIA   |        | C     | D      | E     | F DIA | G       |        | H    |
|----------|---------|---------|--------|-------|--------|-------|-------|---------|--------|------|
|          |         | NOMINAL | ACTUAL |       |        |       |       | NOMINAL | ACTUAL |      |
| CL-00-SB | 1/4-20  | 1/4     | .250   | 3/4   | 1-3/16 | 1-1/2 | 1/2   | 5/16    | .312   | 5/16 |
| CL-0-SB  | 5/16-18 | 5/16    | .312   | 1     | 1-5/8  | 2     | 5/8   | 3/8     | .375   | 3/8  |
| CL-1-SB  | 3/8-16  | 3/8     | .375   | 1-3/8 | 2      | 2-1/2 | 3/4   | 1/2     | .500   | 1/2  |
| CL-2-SB  | 1/2-13  | 1/2     | .500   | 1-3/4 | 2-1/2  | 3-1/8 | 1     | 5/8     | .625   | 5/8  |
| CL-2A-SB |         |         |        | 2-1/4 | 3-1/2  | 4-1/8 |       |         |        |      |
| CL-3-SB  |         |         |        | 1-3/4 | 2-3/4  | 3-1/2 |       |         |        |      |
| CL-3A-SB | 5/8-11  | 5/8     | .625   | 2-1/2 | 4      | 4-3/4 | 1-1/4 | 3/4     | .750   | 3/4  |

METRIC

| PART NO.  | THREAD | THREAD PITCH (mm) | B DIA (mm) | C (mm) | D (mm) | E (mm) | F DIA (mm) | G (mm) | H (mm) |
|-----------|--------|-------------------|------------|--------|--------|--------|------------|--------|--------|
| CLM-00-SB | M6     | 1                 | 6          | 20     | 30     | 40     | 12         | 8      | 10     |
| CLM-0-SB  | M8     | 1.25              | 8          | 25     | 40     | 50     | 16         | 10     | 15     |
| CLM-1-SB  | M10    | 1.5               | 10         | 35     | 50     | 65     | 20         | 12     | 15     |
| CLM-2B-SB | M12    | 1.75              | 12         | 45     | 65     | 80     | 24         | 14     | 15     |
| CLM-2C-SB |        |                   |            | 55     | 90     | 105    |            |        |        |
| CLM-3-SB  | M16    | 2                 | 16         | 45     | 70     | 90     | 32         | 18     | 20     |
| CLM-3A-SB |        |                   |            | 65     | 100    | 120    |            |        |        |

