



ETT-Series, Turntables

ENERPAC

▼ ETT400 Turntable



- Safe and controlled rotation of heavy loads
- Easily change rotation direction
- Dual capacity: 200 ton with one cylinder, 400 ton with two cylinders
- Compact size for use in applications with limited space
- Compatible with standard Enerpac pumps
- Hardwood surface.



▼ SELECTION CHART

Maximum Load Capacity	Model Number	Cylinder Capacity *	Cylinder Oil Capacity *	No. of Cylinders *	Rotation per Stroke	Platform Diameter	
(kN)		(kN)	advance retract		(degrees)	(mm)	(kg)
2000	ETT200	222	792 344	1	12,5	1790	1700
4000	ETT400	222	792 344	2	12,5	1790	1725

* Per cylinder. Cylinder modelnumber: **BRD259-ETT**

ETT Series

Maximum Capacity:

200 - 400 ton

Cylinder Capacity:

25 ton (222 kN)

Maximum Operating Pressure:

700 bar



Safe and controlled rotation

The ETT-Series is your solution for rotating heavy loads during, before or after a lifting and skidding operation.



SFP-Series, Split-Flow Pump

Split-Flow pumps distribute an equal amount of hydraulic oil to a maximum of 8 outlets. Smart valve technology allows both controlled lifting and lowering of heavy loads.

Page: **336**



LH-Series, Low-Height Skidding

The ETT-Series are ideal in combination with our skidding systems, particular the LH-Series. Skidding and rotating in confined spaces is simplified.

Page: **358**



Telescopic Hydraulic Gantries

The ETT-Series in combination with our hydraulic gantry SL-Series makes load handling in the most demanding situations easy.

Page: **356**