

Hydraulic Oil, Manifolds and Fittings

ENERPAC

▼ Shown: HF95T, HF95X, HF95Y



- Maximum pump volumetric efficiency
- Maximum internal heat transfer
- Prevents pump cavitation
- Additives prevent rust, oxidation and sludge
- High viscosity index
- Maximum film protective lubricity.

The Genuine Range

Hydraulic Oil

Contents	Model Number	Use only genuine Enerpac Hydraulic Oil. The use of any other fluid will render your Enerpac warranty null and void.
1 litre	HF95X	
5 litres	HF95Y	
20 litres	HF95T	

▼ OIL SPECIFICATION CHART

Viscosity Index	100 min
Viscosity (cSt @ 40 °C)	32
API Gravity	31-33
Density (cSt @ 15 °C)	875
Flash point	204 °C
Pour point	-32 °C
Colour	Blue
Working Temperature Range	0 - 60 °C
Ideal working temperature	40 °C

700 bar Manifolds

Description	Model Number	Dimensions (mm)
7-port Manifold, short	A64	
7-port Manifold, long allows direct mounting of control valves to the manifold.	A65	
6-port Manifold, hexagon Plugs furnished for all ports 3/8"-18 NPTF.	A66	
Control Manifolds * For control of two or four single-acting cylinders simultaneously. AM21 with 5 ports 3/8"NPTF. AM41 with 7 ports 3/8"NPTF.	AM21 AM41	

* See page 142 for AMGC-Series 4-way manifold assembly complete with gauges.