


Hand Pumps & Hoses

▼ HP350DMIN



- HP-S, HP-D and HP-SD pump ranges are operable at all angles and are highly resistant to accidental spillage of hydraulic fluid. (certified)
- The Single-Port and Twin-Port Hand Pumps are also available with ATEX rating, which are certified for use in hazardous areas II 2G Ex h IIB T5 Gb, II 2D Ex h IIIC T100°C Db.



HP Series



HYDRAULIC SEALED HAND PUMPS

Maximum Pressure Rating:

1st Stage: 13,8 bar 2nd Stage: 700 bar

Pump Type: **2-Speed**

Pump Ratings

The Hydraulic Single Port, Twin Port and Double-Acting Hand-Pump (and hoses) are tailored for use with

hydraulic equipment. Each pump's output is regulated to 700 bar and is delivered from threaded 3/8" NPT output ports. The pumps and hoses can be used with any 700 bar rated hydraulic equipment within their oil capacity specification. The HP range of hydraulic handpumps have been designed with a seal oil reservoir, which allows the pumps to be used in any orientation without the risk of oil spills or air contamination

700 BAR HOSES

AVAILABLE TO PURCHASE SEPARATELY

AVAILABLE TO TOTOTIAGE OLI ATIATLET								
Model Number	Description							
302701-01	HYDRAULIC HOSE 2M							
302702-01	HYDRAULIC HOSE 4M							
302705-01	HYDRAULIC HOSE 3M							
302706-01	HYDRAULIC HOSE 5M							
302707-01	HYDRAULIC HOSE 6M							
1440008-01	ATEX HYDRAULIC HOSE 2M							
1440013-01	ATEX HYDRAULIC HOSE 4M							
1440014-01	ATEX HYDRAULIC HOSE 6M							

Model Number Hand Pump Kit		Type*	I Oil Capacity	e Oil Capacity (cc)	per S	olume troke c) eggs	Handle Effort (kgf)	Piston Stroke (mm)	rall Length (mm)	Dimensions (മாന)	Pump Weight (kg)	t Weight (kg)	Tool Number
Standard	ATEX		Nominal	Useable	1st Stage	2nd St	Max. I	Pisi	Overall (mr	Box	Pur	Ki	Toc
HP350SMIN	HP350SMINEX	SA, SP	350	300	3,62	0,77	33	18	554	250 x 180 x 600	4,4	4,9	HP350S
HP550SMIN	HP550SMINEX	SA, SP	550	580	3,62	0,77	25	18	643	250 x 180 x 700	5,1	5,9	HP550S
HP1000SMIN	HP1000SMINEX	SA, SP	1000	1110	3,62	0,77	21	18	867	250 x 180 x 900	6,1	7,1	HP1000S
HP350DMIN	HP350DMINEX	SA, TP	350	300	3,62	0,77	33	18	580	250 x 180 x 600	6,5	7,2	HP350D
HP550DMIN	HP550DMINEX	SA, TP	550	580	3,62	0,77	25	18	669	250 x 180 x 700	7,2	8,1	HP550D
HP1000DMIN	HP1000DMINEX	SA, TP	1000	1110	3,62	0,77	21	18	893	250 x 180 x 900	7,1	9,3	HP1000D
HP350SDMIN	-	DA	350	300	3,62	0,77	33	18	456	250 x 180 x 600	5,3	5,7	HP350SD
HP550SDMIN	-	DA	550	580	3,62	0,77	25	18	579	250 x 180 x 700	5,7	6,0	HP550SD
HP1000SDMIN	-	DA	1000	1110	3,62	0,77	31	18	769	250 x 180 x 900	5,9	6,3	HP1000SD

SA = Single Acting DA = Double Acting SP = Single Port TP = Twin Port

ENERPAC 🕝

333