HYQUIP

+44 (0)1204 699959 🗞 enquiries@hyquip.co.uk 🖂

hyquip.co.uk

Ultra-High Pressure Hoses & Couplers

- Hose Reel and Stand: Stainless steel stand with 1500 bar hoses from 30 upto 270 metres lengths
- All hose reels are built up with multiple 30 metres length hoses •
- Wide offering of hoses and system components to complete your • tensioning system
- Can be used for subsea fastening systems
- Hoses can be inter-connected in multi-tool set-ups using nipples, • couplers, T-pieces and Y-Pipe assemblies.

| 1500 BAR HOSE | REEL & STANDS | |
|---------------|---------------|-----|
| Model | | Sta |

| Model Number | | Stainless Steel Hose Reels with Stand (Hose with Female Half BR150 and Male Half BH150 couplers) |
|-----------------|-------|---|
| HT15000RS | | Reel & Stand Assembly, No Fittings |
| HT15000HRS | | Hose Reel & Stand, No Hose |
| HT15100HRS | | Hose Reel & Stand, with 30 m hose |
| HT15200HRS | | Hose Reel & Stand, with 60 m hose |
| HT15300HRS | LANA | Hose Reel & Stand, with 90 m hose |
| HT15400HRS | | Hose Reel & Stand, with 120 m hose |
| HT15500HRS | ANX | Hose Reel & Stand, with 150 m hose |
| HT15600HRS | CARD. | Hose Reel & Stand, with 180 m hose |
| HT15700HRS | | Hose Reel & Stand, with 210 m hose |
| HT15900HRS | | Hose Reel & Stand, with 270 m hose |



Hose Lengths: 1 - 30 metres

Hose Reel & Stand: 30 - 270 metres

Maximum Operating Pressure: 1500 bar



Inter-connected with HT-Series hoses Enerpac subsea tensioners apply uniform bolt load.

Complete

Female

Male

| 1500 BAR HOS | 1500 BAR HOSES | | | |
|-----------------|--|------------|------------|--------|
| Model Number | | Hose End 1 | Hose End 2 | Length |
| | | | | (m) |
| HT1503 | 120 | 1/4" BSPM | 1/4" BSPM | 1,0 |
| | - Contraction of the second se | 120° Cone | 120° Cone | |
| HT1510 | 100 | 1/4" BSPM | 1/4" BSPM | 3,0 |
| | | 120° Cone | 120° Cone | |
| HT15100 | | 1/4" BSPM | 1/4" BSPM | 30,0 |
| | | 120° Cone | 120° Cone | |
| HT1503HR * | | BH150 | BR150 | 1,0 |
| HT1506HR * | | BH150 | BR150 | 1,8 |
| HT1510HR * | | BH150 | BR150 | 3,0 |
| HT1520HR * | | BH150 | BR150 | 6,1 |
| HT15100HR * | | BH150 | BR150 | 30,0 |
| HT1503RR * | | BR150 | BR150 | 1,0 |
| HT1506RR * | | BR150 | BR150 | 1,8 |
| HT1510RR * | | BR150 | BR150 | 3,0 |
| HT1520RR * | | BR150 | BR150 | 6,1 |

| (includes dust caps) | 561 | Inan | man |
|---|---------|--------|--------|
| Quick Disconnect Coupler | B150 | BR150 | BH150 |
| Quick Disconnect Coupler & Adaptor Kit | BW150AW | - | - |
| Quick Disconnect Blanking Coupler Set | B150B | BR150B | BH150B |
| 1500 BAR T-PIECES | | | |

1500 BAR COUPLERS

Description

(includes dust cans)

| 1300 DAN I-HEUE3 | | | | |
|------------------|--------------------|----------|----------|----------|
| Model Number | shown HT15TPMMF | End 1 | End 2 | End 3 |
| HT15TPMMF | 1 | 1x BH150 | 1x BH150 | 1x BR150 |
| HT15TPMMM | | 1x BH150 | 1x BH150 | 1x BH150 |

| 1500 BAR Y-PIPE ASSEMBLIES | | | | |
|----------------------------|-----------------------|---------------|---------------|------------------|
| Model Number | shown HT1506YTPMMF | End 1 Hose | End 2 Hose | End 3 T-Piece |
| HT1506YPMMF | a _4 | HT1506HR | HT1506HR | HT15TPMMF |
| HT1510YPMMF | 3, 8-1 | HT1510HR | HT1510HR | HT15TPMMF |
| HT1506YPFMF | | HT1506RR | HT1506RR | HT15TPMMM |
| HT1510YPFMF | 5 2 5 | HT1510RR | HT1510RR | HT15TPMMM |

Y-Pipe Assembly: 1+2 = adaptor; 3 = stainless steel T with 1/4" BSPM 4 = Male Nipple (BH150); 5 = Female Coupling (BR150); 6 = Hose

> ENERPAC. 301

Includes dust caps

H = Male Nipple (BH150); R = Female Coupling (BR150)