

## JH, JHA-Series, Aluminium and Steel Jacks

**ENERPAC**

▼ Shown from left to right: JHA356, JHA156



### JH, JHA Series

Capacity:  
**7 - 100 ton**

Stroke:  
**76 - 155 mm**

Maximum Operating Pressure:  
**700 bar**

- All-directional operation on 7, 15 and 35 ton JHA-series
- Internal relief valve to prevent overloading
- Machined flat front and bottom surfaces permit flush alignment in tight corners
- Chrome plated plungers
- Pumping handle included
- Automatic by-pass port to prevent over-extension (JH-series).



#### Lifting Wedge and Machine Lifts

Ideal to lift the load the first few centimeters. The **LW16** Lifting Wedge requires a very small access gap of only 10 mm.

Page: **182**



#### Load Skates

For moving heavy loads easily and safely.

Page: **184**

| Style           | Jack Capacity<br>ton (kN) | Stroke<br>(mm) | Model Number  | Jack Effective Area<br>(cm <sup>2</sup> ) | Collapsed Height<br>(mm) | Extended Height<br>(mm) | Bottom Plate Dimensions<br>W x L<br>(mm) | Plunger Diameter<br>(mm) | Pump Speed | <br>(kg) |
|-----------------|---------------------------|----------------|---------------|-------------------------------------------|--------------------------|-------------------------|------------------------------------------|--------------------------|------------|-----------------------------------------------------------------------------------------------|
| Aluminium Jacks | 7 (62)                    | 76             | <b>JHA73</b>  | 9,6                                       | 133                      | 209                     | 73 x 158                                 | 30,2                     | Single     | 5,0                                                                                           |
|                 | 15 (133)                  | 153            | <b>JHA156</b> | 20,3                                      | 247                      | 401                     | 92 x 238                                 | 41,4                     | Single     | 13,2                                                                                          |
|                 | 35 (311)                  | 155            | <b>JHA356</b> | 45,6                                      | 257                      | 412                     | 117 x 254                                | 54,1                     | Single     | 18,1                                                                                          |
| Steel Jacks     | 30 (267)                  | 155            | <b>JH306</b>  | 38,3                                      | 254                      | 409                     | 95 x 242                                 | 69,9                     | Single     | 26,8                                                                                          |
|                 | 50 (445)                  | 154            | <b>JH506</b>  | 62,1                                      | 260                      | 414                     | 127 x 258                                | 88,9                     | 2-Speed    | 40,8                                                                                          |
|                 | 100 (890)                 | 153            | <b>JH1006</b> | 133,1                                     | 287                      | 440                     | 181 x 328                                | 130,1                    | 2-Speed    | 74,4                                                                                          |