

Lightweight Hydraulic Foot Pump

P392FP



- Robust, durable and compact
  - Steel frame for maximum stability
  - Steel pumping handle
  - Aluminium reservoir
- Foot pedal lock and lightweight construction for easy carrying
- Two-speed operation reduces foot pedal strokes
- Large foot-pad release valve for controlling load descent
- Internal pressure relief valve for overload protection.


P Series



Reservoir Capacity:  
**492 cm<sup>3</sup>**

Flow at Rated Pressure:  
**2,47 cm<sup>3</sup>/stroke**

Maximum Operating Pressure:  
**700 bar**




**Pump-Cylinder Sets**  
The P392FP is available as set (pump, cylinder, gauge, couplers and hose) for your ordering convenience.

Page: 62



**Hoses**  
Enerpac offers a complete line of high quality hydraulic hoses. To ensure the integrity of your system, specify only genuine Enerpac hydraulic hoses.

Page: 128



Usable Oil Capacity (cm <sup>3</sup> )	Model Number	Pressure Rating (bar)		Oil Displacement per Stroke (cm <sup>3</sup> )		Max. Handle Effort (kg)	Piston Stroke (mm)	Piston Stroke (kg)
		1st stage	2nd stage	1st stage	2nd stage			
492	P392FP *	15	700	11,26	2,47	42	25,4	7,0

\* Available as set, see note on this page.

▼ P392FP offers the advantage of hands free operation to handle and control the tool or cylinder.

