

### **Hydraulic Pump**

# manually operated

## max. operating pressure 100, 200 and 500 bar



Type with foot lever, base and pressure gauge In connection with our clamping elements, workpieces can be clamped economically with this clamping pump.


Furthermore, this pump can be used for lifting loads, adjusting and clamping tables, as well as for other operating processes.

The particular advantages of this pump are:


- Choice of hand or foot operation
- Pumping and releasing with the same lever
- Continuously adjustable pressure relief valve
- Metallic seal on pump piston, thereby nearly wear-free
- Ompact, self-contained design.

Delivery without accessories.


Hydraulic lifting pumps with safety hand or foot lever are assembled and ready for operation. Accessory see page 2.




### Types 8804006, 8805006, 8816006





#### Types 8806006 and 8807006





#### Type 8808006





Included in the delivery of all hydraulic pumps:


- 1 tube male stud coupling D8L or D8S with sieve for swarf protection.
- 1 swivel banjo coupling DSVK8L or SVH8SR with sieve for swarf protection.


Max. operating pressure [bar] 200 100 500 100 200   Oil volume [cm³] 300 300 300 970 970   Available oil volume [cm³] 150 150 150 750 750   Displacement per stroke [cm³] 4 8 2 8 4   Weight [kg] 6.1 6.1 6.1 9.5 9.5	Part no. (without accessory)		8804006	8805006	8816006	8806006	8807006	8808006
Oil volume   [cm³]   300   300   300   970   970     Available oil volume   [cm³]   150   150   150   750   750	Weight	[kg]	6.1	6.1	6.1	9.5	9.5	6.4
Oil volume [cm³] 300 300 970 970	Displacement per stroke	[cm <sup>3</sup> ]	4	8	2	8	4	4
	Available oil volume	[cm <sup>3</sup> ]	150	150	150	750	750	250
Max. operating pressure [bar] 200 100 500 100 200	Oil volume	[cm <sup>3</sup> ]	300	300	300	970	970	400
	Max. operating pressure	[bar]	200	100	500	100	200	200


#### **Accessories**

The following accessories with connecting fittings for the hydraulic pump must be ordered separately:							
For pump type		8804006	8805006	8816006	8806006	8807006	8808006
Base plate	Part no.	3533001	3533001	3533001	-	-	3533001
Bracket	Part no.	3533002	3533002	3533002	-	_	3533002
Flange	Part no.	3533003	3533003	3533003	_	_	3533003
Foot lever	Part no.	0990102	0990102	0990102	0990102	0990102	0990102
Hand lever	Part no.	0990103	0990103	0990103	0990103	0990103	0990103
Pump unit with safety hand lever	Part no.	8804026	8805026	8816026	8806026	8807026	8808026
Pump unit with safety foot lever	Part no.	8804016	8805016	8816016	8806016	8807016	8808016
Pressure gauge with 90° elbow 0-250 bar	Part no.	9811 015	9811 015	-	9811 015	9811 015	9811 015
Pressure gauge with 90° elbow 0-600 bar	Part no.	-	-	9811 017	-	-	-
Hydraulic oil HLP 32, 11 container	Part no.	9895001	9895001	9895001	9895001	9895001	9895001

High-pressure hose see data sheet F 9.361














#### Part no. 0990103



Foot leve


Part no. 0990102





Safety foot leverl \*

\* Delivery only together with hydraulic pump (see table)



#### **Example for ordering**

Hydraulic clamping pump with accessories, 8 cm³ displacement, 100 bar operating pressure

Hydraulic clamping pump	8805006
Foot lever	0990102
Base	3533001
High-pressure hose 1.6 m	9320601600
Gauge with 90° elbow	9811 015
Hydraulic oil	9895001
The pump supplied filled with o	il.

2 Römheld GmbH