

Electric Drives
and Controls

Hydraulics

Linear Motion and
Assembly Technologies

Pneumatics

Service

Rexroth
Bosch Group

Declaration on environmental compatibility in the fields of EMC¹⁾, climate and mechanical stress

RE 30225-U/04.08 1/4

Type VT-MSPA1-50-1X/...

Analog amplifier modules

Product types

- VT-MSPA1-50-1X/V0/ according to data sheet RE 30225
- VT-MSPA1-50-1X/V002/MIL according to data sheet RE 59497

Description of the product family

Analog amplifier modules for controlling direct operated proportional directional valves.

¹⁾ in the sense of the ECM law of 30th August 1995 and Directive 89/336/EEC

The products comply with the following standards:

1. EMC (electromagnetic compatibility)

Testing in accordance with generic standard prEN 50082-2:1996, VDE 0839 part 82-2

EN 61000-4-2:1995 IEC 1000-4-2	VDE 0847-4-2	ESD (electrostatic discharge)	Air discharge: Severity 3 / assessment criterion A Contact discharge: Severity 4 / assessment criterion A
EN 61000-4-4:1995 IEC 1000-4-4	VDE 0847-4-4	BURST (transient discharge)	Supply voltage to: Severity 2 / assessment criterion A Severity 3 / assessment criterion B Data cable: Severity 4 / assessment criterion A
EN 61000-4-5:1995	VDE 0847-4-5	SURGE (surge voltages)	Supply voltage: Severity 1 / assessment criterion B
EN 61000-4-6:1996 IEC 1000-4-6	VDE 0847-4-6	HF fields, conducted interference	Severity 3 assessment criterion A

2. Climate

Testing in accordance with EN 60068-2 / IEC 68-2 (environmental test)

Details in () are applied for VT-MSPA1-50-1X/V002/MIL

EN 60068-2-1:1994		Cold test	2 cycles at -25 °C (-5 °C) Dwell time 2 hours
EN 60068-2-2:1993		Dry heat test	2 cycles at +55 °C (+70 °C) Dwell time 2 hours
EN 60068-2-1:1994 EN 60068-2-2:1993		Storage temperature	-25 °C, dwell time 16 hours +85 °C, dwell time 16 hours
	IEC 68-2-14:1986	Temperature cycle	2 cycles at -25 °C to +55 °C (-5 to +70 °C) Dwell time 3 hours each at min. / max. temperature
	IEC 68-2-30:1985 (IEC 60068-2-30:1999)	Damp heat, cyclical	Variant 2 +25 °C to +40 °C 93 % to 97 % relative humidity 2 cycles of 24 hours each

The products comply with the following standards (continued):

3. Mechanical stress

Vibration and shock test in accordance with EN 60068-2 / IEC 68-2 / DIN 40046 (environmental test)
Testing in three axes (X/Y/Z)

prEN 60068-2-6:1994			Sine test	10 cycles, 5...500 Hz...5 Hz at a logarithmic frequency change rate of 1 oct./min. 5 to 57 Hz, amplitude 0.3 mm (p-p) 57 to 500 Hz, amplitude 2 g 15 to 30 min dwell time at resonance frequency (data per axis)
	IEC 68-2-36:1973	DIN 40046-24:1977	Random test	20 to 500 Hz, amplitude 0.01 g ² /Hz (2.2 g RMS) Testing time 30 min (data per axis)
EN 60068-2-27:1993			Shock test	Half sine 15 g / 11 ms, 3 x in positive/ 3 x in negative direction per axis; 18 individual shocks in total

© This document, as well as the data, specifications and other information set forth in it, are the exclusive property of Bosch Rexroth AG. It may not be reproduced or given to third parties without its consent. The data specified above only serve to describe the product. No statements concerning a certain condition or suitability for a certain application can be derived from our information. The information given does not release the user from the obligation of own judgment and verification. It must be remembered that our products are subject to a natural process of wear and aging.