

Electric Drives
and Controls

Hydraulics

Linear Motion and
Assembly Technologies

Pneumatics

Service

Rexroth
Bosch Group

Declaration on environmental compatibility in the field of EMC¹⁾ and climate

RE 29014-U/04.06 1/4

Type STW 0195 and STW 0196

3-way proportional directional valve, direct operated with, pQ-functionality

Description of the product

- Direct operated 3-way proportional directional valve with integrated digital electronic and integrated pressure sensor.
- Integrated Axis Controller for pressure control in port A and Fieldbus interface.

Features:

- Open-loop flow control
- Closed-loop pressure control
- p/Q-Functionality

¹⁾ as defined by EMC dated 30th August 1995 and Directive 89/336/EEC

The above mentioned products comply with the following basic standards

1. EMC (electromagnetic compatibility)

EN 61000-6-2:2001	VDE 0839 part 6-2	Field basic standard	Interference immunity
EN 61000-4-2:1995 +A1:1998 +A2:2000 IEC 1000-4-2	VDE 0847-4-2	ESD (electrostatic discharge)	Air discharge up to: Severity 4 / assessment criterion A Contact unloading: Severity 4 / assessment criterion A
EN 61000-4-3:1996 +A1:1998 +A2:2001 IEC 1000-4-3	VDE 0847-4-3	HF-Fields	Severity grade 3 / assessment criterion A 10 V/m, 80...1000 MHz Severity grade 3 / assessment criterion A 10 V/m, 1...2.5 GHz
EN 61000-4-4:2004 IEC 1000-4-4	VDE 0847-4-4	BURST (transient interference)	Repetition rate 5 KHz Power supply: Severity grade 3 / assessment criterion A Data lines up to: Severity grade 4 / assessment criterion A Repetition rate 100 KHz Power supply: Severity grade 3 / assessment criterion A Data lines up to: Severity grade 4 / assessment criterion A
EN 61000-4-5:1995 +A1:2001 IEC 1000-4-5	VDE 0847-4-5	SURGE (surge voltage)	Power supply : Severity grade 1 / assessment criterion A
EN 61000-4-6:1996 +A1:2001 IEC 1000-4-6	VDE 0847-4-6	HF-Fields, conducted interference	Severity grade 3 / assessment criterion A
EN 61000-6-4:2001	VDE 0839 part 6-4	Field basic standard	Interference emitted
EN 55011:1998 A1:1999+A2:2002	VDE 0875-11	Emission Interference voltage	Class A / 0.15...30 MHz
EN 61000-6-3:2001	VDE 0839 part 6-3	Field basic standard	Interference emitted
EN 55022:1998 A1:2000+A2:2003	VDE 0878-22	Emission Interference voltage	Class B* / 0.15...30 MHz * with power supply VT-NE40 used (Mat.-No. R900782039)
EN 55022:1998 +Corr2001+A1:2000	VDE 0878-22	Emission noise field strength	Class B / 30...1000 MHz

2. Climate

EN 60068-2	IEC 68-2		Environmental test
EN 60068-2-1:1994		Cold test	2 cycles -25 °C dwell time 2 hours
EN 60068-2-2:1993		Dry heat test	2 cycles +65 °C dwell time 2 hours
EN 60068-2-1:1994 EN 60068-2-2:1993		Storage temoerature	-25 °C dwell time 16 hours +85 °C dwell time 16 hours
	IEC 68-2-14:1986	Temperature cycle	2 cycles -25 °C to +65 °C dwell time 3 hours at min./max. temperature
	IEC 68-2-30:1985	Damp heat, cyclical	Variant 2 +25 °C to +55 °C 93 % to 97 % relative humidity 2 cycles of 24 hours

3. Protection test (IP)

EN 60529	DIN VDE 0470 Part 1, Point 14		Protection test (IP)
EN 60529:1991	DIN VDE 0470, part 1	International Protection	X5 water jet protected with mounted and bolted cable connectors

Notes

© This document, as well as the data, specifications and other information set forth in it, are the exclusive property of Bosch Rexroth AG. It may not be reproduced or given to third parties without its consent.

The data specified above only serve to describe the product. No statements concerning a certain condition or suitability for a certain application can be derived from our information. The information given does not release the user from the obligation of own judgment and verification. It must be remembered that our products are subject to a natural process of wear and aging.