

Electric Drives
and Controls

Hydraulics

Linear Motion and
Assembly Technologies

Pneumatics

Service

Rexroth
Bosch Group

Declaration on environmental compatibility in the fields of EMC¹⁾, climate and mechanical stress

RE 30523-U/09.07 1/4
Replaces: 06.06

Typ VT-VSPD-1-2X

Digital valve amplifier for proportional valves
without electrical position feedback

Product types

– VT-VSPD-1-2X/V0/...-0-1 according to data sheet RE 30523

Description of the product family

Digital valve amplifier for valves without position feedback

¹⁾ in the sense of the EMC law dated 30th August 1995 and Directive 89/336/EEC)

The above products comply with the following standards:

1. EMC (electromagnetic compatibility)

Testing according to specialized basic standard EN 61000-6-2:2001, VDE 0839 part 6-2

EN 61000-4-2:1995 +A1:1998 +A2:2000 IEC 1000-4-2	VDE 0847-4-2	ESD (electrostatic discharge)	Air discharge: Severity 3 / assessment criterion A Contact discharge: Severity 4 / assessment criterion A
EN 61000-4-4:2004 IEC 1000-4-4	VDE 0847-4-4	BURST (transient discharge)	Repetition rate 5 kHz and 100 kHz: Supply voltage: Severity 2 / assessment criterion A Severity 3 / assessment criterion B Data cable up to: Severity 4 / assessment criterion A
EN 61000-4-5:1995 +A1:2001 IEC 1000-4-5	VDE 0847-4-5	SURGE (surge voltages)	Supply voltage: Severity 1 / assessment criterion A
EN 61000-4-6:1996 +A1:2001 IEC 1000-4-6	VDE 0847-4-6	RF fields conducted interference	Severity 3 / assessment criterion A

2. Climate

Testing according to EN 60068-2 / IEC 68-2 (Environmental test)

EN 60068-2-1:1994		Cold test	2 cycles -5 °C Dwell time 2 hours
EN 60068-2-2:1993		Dry heat test	2 cycles +55 °C Dwell time 2 hours
EN 60068-2-1:1994 EN 60068-2-2:1993		Storage temperature	-25 °C, dwell time 16 hours +85 °C, dwell time 16 hours
	IEC 68-2-14:1986	Temperature cycle	2 cycles -5 °C to +55 °C Dwell time 3 hours each at min. / max. temperature
EN 60068-2-30:1999		Damp heat, cyclical	Variant 2 +25°C to + 40°C 93 % to 97 % relative humidity 2 cycles, 24 hours each

The above products comply with the following standards (continued):

3. Mechanical stress

Vibration and shock test according to EN 60068-2 / IEC 68-2 / DIN 40046 (Environmental test)
 Tests were carried out in three axes (X/Y/Z)

EN 60068-2-6:1996			Sine test	10 cycles, 5 to 500 Hz to 5 Hz at a logarithmic frequency change rate of 1 oct./min. 5 to 57 Hz, amplitude 0.3 mm (p-p) 57 to 500 Hz, amplitude 2 g
EN 60068-2-64:1995	IEC 68-2-36:1973	DIN 40046-24:1977	Random test Broadband-noise	20 to 2000 Hz, amplitude 0.01 g ² / Hz (2.2 g RMS), testing time 30 min
EN 60068-2-27:1993			Shock test	Half sine 15 g / 11 ms, 3 x in positive / 3 x in negative direction per axis; in total, 6 individual shocks

© This document, as well as the data, specifications and other information set forth in it, are the exclusive property of Bosch Rexroth AG. It may not be reproduced or given to third parties without its consent.
The data specified above only serve to describe the product. No statements concerning a certain condition or suitability for a certain application can be derived from our information. The information given does not release the user from the obligation of own judgment and verification. It must be remembered that our products are subject to a natural process of wear and aging.