




## Inline Filter DFN/DFNF/LFN/LFNF to DIN 24550

up to 350 l/min, up to 400 bar



### 1. TECHNICAL SPECIFICATIONS

#### 1.1 FILTER HOUSING

##### Construction

The filter housings are designed in accordance with international regulations. They consist of a filter head and a screw-in filter bowl. DFN/F and LFNF filters are suitable for flow in both directions.

Standard equipment:

- without bypass valve
- connection for a clogging indicator

#### 1.2 FILTER ELEMENTS

HYDAC filter elements are validated and their quality is constantly monitored according to the following standards:

- ISO 2941
- ISO 2942
- ISO 2943
- ISO 3724
- ISO 3968
- ISO 11170
- ISO 16889 Filter elements are available with the following pressure stability values: Betamicon® (BN4HC): 20 bar Betamicon® (BH4HC): 210 bar Wire mesh (W/HC): 20 bar

#### 1.3 FILTER SPECIFICATIONS

|  |  |  |
|--|--|--|
| Nominal pressure                           | 100 bar  | : all LFN and LFNF                         |
|  | 210 bar  | : DFN 160, 400                             |
|  | 400 bar  | : DFN 40, 63, 100, 250<br>DFNF 40, 63, 100 |
| Fatigue strength                           | At nominal pressure 10 <sup>6</sup> cycles from 0 to nominal pressure  |  |
| Temperature range                          | -30 °C to +100 °C<br>(-30 °C to -10 °C = 200 bar - only DFN/F)   |  |
| Material of filter head (and cover plate)  | EN-GJS-400-15: DFN/F<br>Aluminium : LFN/F Steel  |  |
| Material of filter bowl (tube)             | : DFN/F<br>Aluminium : LFN/F 40, 63<br>Steel : LFN/F 100   |  |
| Type of indicator                          | VM (Diff. pressure ind. up to 210 bar oper. pressure - not for type LZ)<br>VD (Diff. pressure ind. up to 420 bar oper. pressure) |  |
| Pressure setting of the clogging indicator | 5 bar (others on request)  |  |
| Bypass cracking pressure (optional)        | 7 bar (others on request)  |  |

#### 1.4 SEALS

NBR (=Perbunan)

#### 1.5 INSTALLATION

Inline filter

#### 1.6 SPECIAL MODELS AND ACCESSORIES

- With bypass valve
- FPM seals

#### 1.7 SPARE PARTS

See Original Spare Parts List

#### 1.8 CERTIFICATES AND APPROVALS

On request


#### 1.9 COMPATIBILITY WITH HYDRAULIC FLUIDS ISO 2943

- Hydraulic oils H to HLPD DIN 51524
- Lubrication oils DIN 51517, API, ACEA, DIN 51515, ISO 6743
- Compressor oils DIN 51506
- Biodegradable operating fluids VDMA 24568 HETG, HEES, HEPG
- Fire-resistant fluids HFA, HFB, HFC and HFD
- Operating fluids with high water content (>50% water content) on request


#### 1.10 IMPORTANT INFORMATION

- Filter housings must be earthed.
- When using electrical clogging indicators, the electrical power supply to the system must be switched off before removing the clogging indicator connector.

#### Symbol for hydraulic systems DFN / LFN



DFNF/  
LFNF



## 2. MODEL CODE (also order example)

DFN BN/HC 250 S F 10 D 1 . X /-L24

### 2.1 COMPLETE FILTER

#### Filter type

DFN, LFN, LFNF, DFNF

#### Filter material of element

BN/HC Betamicon® (BN4HC) BH/HC Betamicon® (BH4HC)  
W/HC Wire mesh

#### Size of filter or element

DFN: 40, 63, 100, 160\*, 250, 400 (\*on request)

DFNF: 40, 63, 100

LFN/F: 40, 63, 100

#### Operating pressure

I = 100 bar (LFN and LFNF)

L = 210 bar (DFN 160, 400)

S = 400 bar (DFN 40, 63, 100, 250; DFNF 40, 63, 100)

#### Type and size of connection

| Type | Connection | Filter size |    |     |     |     |     | to DIN 24550 (●);<br>possible ports (x) |
|------|------------|-------------|----|-----|-----|-----|-----|---|
|      |            | 40          | 63 | 100 | 160 | 250 | 400 |   |
| B    | G 1/2      | ●           | x  |     |     |     |     |   |
| G    | G 3/4      | x           | ●  | x   |     |     |     |   |
| D    | G 1        | x           | x  | ●   |     |     |     |   |
| E    | G 1 1/4    |             |    |     | ●   | x   |     | x                                       |
| F    | G 1 1/2 x  |             |    |     |     | ●   | x   | ●                                       |
| K    | DN 40*     |             |    |     | x   |     |     |   |

\*Flange SAE, 6000 PSI

#### Filtration rating in µm

BN/HC, BH/HC: 3, 6, 10, 25 W/HC: 25, 50, 100, 200

#### Type of clogging indicator

Y plastic blanking plug in indicator port

A steel blanking plug in indicator port

B visual

C electrical

D visual and electrical

LZ visual-mechanical / electrical

for other clogging indicators,  
see brochure no. 7.050../..

#### Type code

1 DFN / DFNF

2 LFN / LFNF

#### Modification number

X the latest version is always supplied

#### Supplementary details

B. bypass cracking pressure (e.g. B7 = 7 bar); without details = without bypass valve

L... light with appropriate voltage (24V, 48V, 110V, 220V)

LED 2 light emitting diodes up to 24 volts

AV LZ indicator with plug to AUDI and VW specification

BO LZ indicator with plug and pin connections to BMW and Opel specification (M12x1)

CN LZ indicator with plug to DIN 43651 with 3 LEDs (CNOMO specification)

DB LZ indicator with plug to DIN 43651 with 3 LEDs (Daimler-Benz specification)

D4C LZ with plug and connector to Daimler-Chrysler specification and cold start suppression 30°C

BO-LED as for BO, but with diode strip

SO368 inlet and outlet G 1/2 (without RI connection; only for DFN/F 40, 63, 100)

V FPM seals

W suitable for HFA and HFC emulsions

### 2.2 REPLACEMENT ELEMENT

0250 DN 010 BN4HC /-V

#### Size

0040, 0063, 0100, 0160, 0250, 0400

#### Type

DN

#### Filtration rating in µm

BN4HC, BH4HC: 003, 006, 010, 025

W/HC: 025, 050, 100, 200

#### Filter material

BN4HC, BH4HC, W/HC

#### Supplementary details

V (for descriptions, see Point 2.1)

### 2.3 REPLACEMENT CLOGGING INDICATOR

VM 5 D . X /-L24

#### Type of indicator

VM differential pressure indicator up to 210 bar operating pressure (not for type LZ)

VD differential pressure indicator 420 bar operating pressure

#### Pressure setting

5 standard 5 bar, others on request

#### Type of clogging indicator (see Point 2.1)

#### Modification number

X the latest version is always supplied

#### Supplementary details

L..., LED, V, W (for descriptions, see Point 2.1)

3. FILTER CALCULATION / SIZING

The total pressure drop of a filter at a certain flow rate Q is the sum of the housing Δp and the element Δp and is calculated as follows:

Δ p<sub>total</sub> = Δp<sub>housing</sub> + Δp<sub>element</sub>

Δp<sub>housing</sub> = (see Point 3.1)

Δp<sub>element</sub> = Q •  $\frac{SK}{1000}$  •  $\frac{viscosity}{99}$   
(\*see Point 3.2)


For ease of calculation, our Filter Sizing Program is available on request free of charge.

NEW: Sizing online at [www.hydac.com](http://www.hydac.com)


3.1 Δp-Q HOUSING CURVES BASED ON ISO 3968

The housing curves apply to mineral oil with a density of 0.86 kg/dm³ and a kinematic viscosity of 30 mm²/s. In this case, the differential pressure changes proportionally to the density.


DFN 40, 63, 100  
LFN 40, 63, 100



DFNF / LFNF 40, 63, 100



DFN 160, 250, 400




3.2 GRADIENT COEFFICIENTS (SK) FOR FILTER ELEMENTS

The gradient coefficients in mbar/(l/min) apply to mineral oils with a kinematic viscosity of 30 mm²/s. The pressure drop changes proportionally to the change in viscosity.

| LFN/F<br>DFN/F | BN4HC |      |       |       |
|----------------|-------|------|-------|-------|
|                | 3 μm  | 6 μm | 10 μm | 25 μm |
| 40             | 40.4  | 24.8 | 16.4  | 10.9  |
| 63             | 29.0  | 18.2 | 11.7  | 7.6   |
| 100            | 19.0  | 11.7 | 7.7   | 5.3   |
| 160            | 8.0   | 5.1  | 3.8   | 2.5   |
| 250            | 5.4   | 3.4  | 2.8   | 1.9   |
| 400            | 3.4   | 2.1  | 1.7   | 1.1   |

| LFN/F<br>DFN/F | BH4HC |      |       |       | W/HC  |
|----------------|-------|------|-------|-------|-------|
|                | 3 μm  | 6 μm | 10 μm | 25 μm |       |
| 40             | 40.4  | 24.8 | 16.4  | 10.9  | 0.966 |
| 63             | 29.0  | 18.2 | 11.7  | 7.6   | 0.540 |
| 100            | 19.0  | 11.7 | 7.7   | 5.3   | 0.325 |
| 160            | 8.0   | 5.1  | 3.8   | 2.5   | 0.168 |
| 250            | 5.4   | 3.4  | 2.8   | 1.9   | 0.101 |
| 400            | 3.4   | 2.1  | 1.7   | 1.1   | 0.061 |

## LFN, LFNF



| Type     | Weight incl. element [kg] | Volume of pressure chamber [l] |
|----------|---------------------------|--------------------------------|
| LFN 40   | 1.45                      | 0.26                           |
| LFN 63   | 1.8                       | 0.40                           |
| LFN 100  | 4.3                       | 0.50                           |
| LFNF 40  | 1.45                      | 0.26                           |
| LFNF 63  | 1.8                       | 0.40                           |
| LFNF 100 | 4.3                       | 0.50                           |
| DFN 40   | 5.0                       | 0.22                           |
| DFN 63   | 6.0                       | 0.33                           |
| DFN 100  | 6.25                      | 0.50                           |
| DFN 160  | 20.0                      | 1.10                           |
| DFN 250  | 22.0                      | 1.70                           |
| DFN 400  | 26.5                      | 2.70                           |
| DFNF 40  | 5.0                       | 0.22                           |
| DFNF 63  | 6.0                       | 0.33                           |
| DFNF 100 | 6.25                      | 0.50                           |

| Type     | b1                 | b2 | b3 | d1 | d2   | d3  | d4  | d5 | d6 | d7 | h1 | h2    | h3 | h4 | h5 | SW1 | SW2 | t1 | t2 | t3   |   |
|----------|--------------------|----|----|----|------|-----|-----|----|----|----|----|-------|----|----|----|-----|-----|----|----|------|---|
| LFN 40   | 90                 | 56 | 32 | 84 | 68   | G ½ | 34  | M6 | 52 | 48 | 90 | 57    | 39 | 6  | 75 | 27  | 27  | 1  | 14 | 9    |   |
| LFN 63   | 90                 | 56 |    | 32 | 84   | 68  | G ¾ | 44 | M6 | 52 | 48 | 150   | 57 | 39 | 6  | 75  | 27  | 27 | 1  | 17   | 9 |
| LFN 100  | 160 <sup>(*)</sup> | 56 | 32 | 84 | 65   |     | G 1 | -  | M6 | 52 | 48 | 245.5 | 57 | 39 | 6  | 75  | 27  | 27 | -  | 24.5 | 9 |
| LFNF 40  | 90                 | 56 | 32 | 84 | 68.2 |     | G ½ | 34 | M6 | 52 | 48 | 90    | 57 | 39 | 6  | 75  | 27  | 27 | 1  | 14   | 9 |
| LFNF 63  | 90                 | 56 | 32 | 84 | 68.2 |     | G ¾ | 44 | M6 | 52 | 48 | 150   | 57 | 39 | 6  | 75  | 27  | 27 | 1  | 17   | 9 |
| LFNF 100 | 160 <sup>(*)</sup> | 56 | 32 | 84 | 65   |     | G 1 | -  | M6 | 52 | 48 | 245.5 | 57 | 39 | 6  | 75  | 27  | 27 | -  | 24.5 | 9 |

Version DFN...S C (G3/4): 150  
Version DFN...S B (G1/2): 114

size 63, 100, 145, 50  
size 100, 237

size 63, 145, 50  
size 100, 237  
size 40, 86

vent (AF width 5)  
test point  
G 1/8

SW 27

SW 27

Ø 68, 20 (size 100)  
Ø 65

4 x M6 / 9 deep

inlet

outlet

port for clogging indicator

oil drain  
AF width 10

DN...S C: G3/4, 22 deep  
DN...S B: G1/2, 14 deep

Version DFN  
40/63/100 S D (G1)  
DFN...S B.-/SO368:92

96  
92

7

39

85

14

56

32

41 (839)

[illegible]

The information in this brochure relates to the operating conditions and applications described.  
For applications or operating conditions not described, please contact the relevant technical department.  
Subject to technical modifications.