



Part Number 263304, Rubber Body For Buegu Clamp

Buegu clamps are ideal for mobile applications where space is limited. They absorb shock and vibration, and reduce noise.



[Specifications](#) | [Dimensions](#) | [Features](#) | [Note](#)

Specifications		
Type	Buegu Clamps	
Model Code Description	HRBGS 2 GT 16-16 TPE73	
Number of Tubes	2	
Stirrup and Weld Plate	Carbon Steel	
Clamp Body	Thermoplastic Elastomer (Santoprene TPE 73)	
Minimum Temperature	-40 °C	-40 °F
Maximum Temperature	125 °C	257 °F
Series	HRBGS	
Clamp Size	2	
Application	Rubber Body for Buegu Clamp	
Metal Components Material	Carbon Steel	
BUn	EA	
Division	ACCESSORIES	
Product Group Family	MOUNTING COMPONENTS	
Product	CLAMPS	

Dimensions

Tube O.D.	5/8 in	3/4 in
Pipe Size	3/8 in	
Bore Diameter D11	0 in 16 mm	
Bore Diameter D22	0.625 in	16 mm
Dimension A1	1 in 35 mm	
Dimension A2	2.32 in	59 mm
Dimension H1	0 in 12 mm	
Dimension H2	1.03 in	27 mm
Dimension B	0.78 in	
	20 mm	



- Low Profile Design
- Shock and vibration reduction
- Easy installation

Note

Consult factory for different bore diameters

1. Dimensions are in inches (mm).
2. Dimensions are for general information only, all critical dimensions should be verified by requesting a certified print.

1 Consult factory for sizes 1 and 2 with different bore diameters.
2 Consult factory for sizes 1 and 2 with different bore diameters.