




Inline Filter RFL Welded Version up to 15000 l/min, up to 16 bar



1. TECHNICAL SPECIFICATIONS

1.1 FILTER HOUSING Construction

The filter housings are designed in accordance with international regulations. They consist of a two-piece filter housing with a bolt-on cover plate.

Standard equipment:

- stand
- with bypass valve
- inlet and outlet are positioned at different heights on opposite sides
- connections for venting and draining
- connection for a clogging indicator

1.2 FILTER ELEMENTS

HYDAC filter elements are validated and their quality is constantly monitored according to the following standards:

- ISO 2941, ISO 2942, ISO 2943
- ISO 3724, ISO 3968, ISO 11170
- ISO 16889

Number of filter elements

RFL	Elements
130x	1x1300 R
132x	1x2600 R
250x	3x0850 R
252x	3x1700 R
400x	5x0850 R
402x	5x1700 R
520x	4x1300 R
522x	4x2600 R
650x	5x1300 R
652x	5x2600 R
780x	6x1300 R
782x	6x2600 R
1500x	10x1300 R
1502x	10x2600 R

Filter elements are available with the following pressure stability values:

Optimicon® (ON):	20 bar
Optimicon® Power (ON/PO):	10 bar
Paper (P/HC): Stainl. st. wire	10 bar
mesh (W/HC):	20 bar
Stainless steel fibre (V):	30 bar
Betamicon®/Aquamicon® (BN4AM):	10 bar
Aquamicon® (AM):	10 bar

1.3 FILTER SPECIFICATIONS

Nominal pressure	16 bar
Temperature range	-10 °C to +100 °C
Material of filter housing and cover plate	RFL 1300 to 15020: Welded steel RFL 1303 to 15023: Stainl. st. 1.4571
Type of clogging indicator	VM (differential pressure measurement up to 210 bar operating pressure)
Pressure setting of the clogging indicator	2 bar (others on request)
Bypass cracking pressure	3 bar (others on request)

1.4 SEALS

NBR (=Perbunan)

1.5 INSTALLATION

Inline filter

1.6 SPECIAL MODELS AND ACCESSORIES

- Without bypass valve
- Drain and vent ports with ball valves or other shut-off valves
- Inlet and outlet positioned one above the other
- Counter flanges available for all sizes
- Venting line with sight gauges
- Cover plate lifting device

1.7 SPARE PARTS

See Original Spare Parts List

1.8 CERTIFICATES AND APPROVALS

Material code (final digit of filter size) - 1:

These filters can be supplied with manufacturer's test certificates O and M to DIN 55350, Part 18. Test certificates 3.1 to DIN EN 10204.

Material code (final digit of filter size) - 3:

Filters for use in separation technology with low viscosity, high viscosity and aggressive fluids as well as gaseous media.*


* These filters are available from HYDAC P
COMPATIBILITY WITH HYDRAULIC FL

- Hydraulic oils H to HLPD DIN 51524
- Lubrication oils DIN 51517, API, ACEA, DIN 51515, ISO 6743
- Compressor oils DIN 51506
- Biodegradable operating fluids VDMA 24568 HETG, HEES, HEPG
- Fire-resistant fluids HFA, HFB, HFC and HFD
- Operating fluids with high water content (>50% water content) on request

1.10 IMPORTANT INFORMATION

- Filter housings must be earthed.
- When using electrical clogging indicators, the electrical power supply to the system must be switched off before removing the clogging indicator connector.
- Filters must be flexibly mounted and not fixed rigidly to the floor or used as a pipe support.

Symbol for hydraulic systems



2. MODEL CODE (also order example)

RFL ON 1300 C K 10 D 1 . X /-L24

2.1 COMPLETE FILTER

Filter type

RFL

Filter material

ON Optimicron® ON/PO P/HC Paper W/HC Stainl. st. AM Aquamicon®
Optimicron® Power* wire mesh BN/AM Betamicon®/Aquamicon®
V Stainless steel fibre

Size of filter or element

RFL: 1300, 1303, 1320, 1323, 2500, 2503, 2520, 2523, 4000, 4003, 4020, 4023, 5200, 5203,
5220, 5223, 6500, 6503, 6520, 6523, 7800, 7803, 7820, 7823, 15000, 15003, 15020, 15023

Operating pressure

C = 16 bar

Type and size of connection

Type	Port	Filter size							
		1300	1320	2500	4000	5200	6500	7800	15000
		1303	1323	2503	4003	5203	6503	7803	15003
				2520	4020	5220	6520	7820	15020
				2523	4023	5223	6523	7823	15023
K	DIN DN 40	•	•						
L	DIN DN 50	•	••						
M	DIN DN 65	•	•	•					
Q	DIN DN 80	•	•	•	•	•			
R	DIN DN 100	•	•	•	•	•	•	•	
U	DIN DN 125		•	•	•	•	•	•	
V	DIN DN 150			•	•	•	•	•	
W	DIN DN 200				•	•	•••		•
X	DIN DN 250					•		•	•
Y	DIN DN 300								•

Filtration rating in µm 1, 3, 5,

ON: 15, 20 P/HC: 10, 20 W/HC: 25, BN/AM: 3, 10
ON/PO*, V: 3, 5, 10, 20 50, 100, 200 AM: 40

Type of clogging indicator

Y plastic blanking plug in indicator port

A stainless steel blanking plug in indicator port

B visual

C electrical

D visual and electrical

for other clogging indicators,
see brochure no. 7.050../..

Type code

1

Modification number

X the latest version is always supplied

Supplementary details

B. special cracking pressure of bypass (e.g. B1 = 1 bar)

DH cover plate lifting device

KB without bypass valve L... light with appropriate voltage

(24V, 48V, 110V, 220V)

LED 2 light emitting diodes up to 24 Volt

OR O-ring groove on the DIN flange (inlet and outlet) to Rexroth standard AB 22-04

RE sealing strip E on the flange (inlet and outlet): surface finish 3.6 µm

V FPM seals

33 inlet and outlet positioned one above the other

only for clogging indicators
type "D"

2.2 REPLACEMENT ELEMENT

1300 R 010 ON /-V

Size

0850, 1300, 1700, 2600

Type

R

Filtration rating in µm

ON: 001, 003, 005, 010, 015, 020 W/HC: 025, 050, 100, 200 BN4AM: 003, 010
ON/PO*, V: 003, 005, 010, 020 P/HC: 010, 020 AM: 040

Filter material

ON, ON/PO*, V, W/HC, P/HC, BN4AM, AM

Supplementary details

V (for descriptions, see point 2.1)

2.3 REPLACEMENT CLOGGING INDICATOR

VM 2 D . X /-L24

Type

VM differential pressure indicator up to 210 bar operating pressure

Pressure setting

2 standard 2 bar, others on request

Type of clogging indicator (see Point 2.1)

Modification number

X the latest version is always supplied

Supplementary details

L..., LED, V (for descriptions, see point 2.1)

* Optimicron® Power only in filtration ratings 5, 10 and 20 µm

3. FILTER CALCULATION / SIZING

The total pressure drop of a filter at a certain flow rate Q is the sum of the housing Δp and the element Δp and is calculated as follows:

$$\Delta p_{\text{total}} = \Delta p_{\text{housing}} + \Delta p_{\text{element}}$$

$$\Delta p_{\text{housing}} = (\text{see Point 3.1}) \Delta p = Q$$

$$\cdot \frac{\text{SK}^*}{30} \cdot \frac{\text{viscosity}_{\text{element}}}{1000}$$

(*see point 3.2)


For ease of calculation, our Filter Sizing Program is available on request free of charge.

NEW: Sizing online at www.hydac.com


3.1 Δp -Q HOUSING CURVES BASED ON ISO 3968

The housing curves apply to mineral oil with a density of 0.86 kg/dm^3 and a kinematic viscosity of $30 \text{ mm}^2/\text{s}$. In this case, the differential pressure changes proportionally to the density.


RFL 1300, 1303




RFL 1320, 1323




RFL 2500, 2503, 2520, 2523




RFL 4000, 4003, 4020, 4023




RFL 5200, 5203, 5220, 5223




RFL 6500, 6503, 6520, 6523



RFL 7800, 7803, 7820, 7823



RFL 15000, 15003, 15020, 15023



3.2 GRADIENT COEFFICIENTS (SK) FOR FILTER ELEMENTS


The gradient coefficients in mbar/(l/min) apply to mineral oils with a kinematic viscosity of $30 \text{ mm}^2/\text{s}$. The pressure drop changes proportionally to the change in viscosity.

RFL	ON						ON/PO		
	1 μm	3 μm	5 μm	10 μm	15 μm	20 μm	5 μm	10 μm	20 μm
850	2.77	1.31	1.00	0.58	0.44	0.36	0.28	0.24	0.16
1300	1.72	0.72	0.59	0.35	0.32	0.22	0.18	0.15	0.10
1700	1.35	0.64	0.53	0.28	0.25	0.18	0.13	0.11	0.07
2600	0.84	0.36	0.29	0.18	0.16	0.11	0.08	0.07	0.05


RFL	V				W/HC
	3 μm	5 μm	10 μm	20 μm	
850	0.8	0.6	0.4	0.3	0.052
1300	0.5	0.4	0.3	0.2	0.048
1700	0.4	0.3	0.2	0.1	0.025
2600	0.3	0.2	0.1	0.1	0.017

4. DIMENSIONS

RFL 1300 - 1320



RFL 2500 - 15020



RFL	Flange port	b1	b2	d1	d2	d3	h1	h2	h3	h4	h5	h7 including	Weight pressure element [kg]	Volume of chamber [l]
130x/132x	DIN DN 40	412	260	250	219.1	340	972/1416	370	294	212	384/824	500/940	64.1/78.1	18/33
	DIN DN 50								266	240	384/824		64.1/78.1	18/33
	DIN DN 65								279	227	384/824		65.1/79.1	18/33
	DIN DN 80								266	240	384/824		67.1/81.1	19/34
	DIN DN 100								253	275	362/802		69.1/83.1	19/34
132x	DIN DN 125	480	260	250	219.1	340	/1416	370	215	291	/824	/940	87.1	/36
250x/252x	DIN DN 50	466	312	250	273	360	942/1332	220	378	270	222/612	420/810	73.9/82.4	34/54
	DIN DN 65						990/1380		408	350	160/550		70.9/85.4	36/56
	DIN DN 80						990/1380		388	410	120/510		72.9/87.4	36/56
	DIN DN 100						1050/1440		438	304	236/626		75.9/90.4	40/60
	DIN DN 125						1050/1440		438	380	160/550		79.9/94.4	40/60
400x/402x	DIN DN 150	600	-	330	355.6	460	1050/1440	266	438	365	175/565	420/810	83.9/98.4	45/65
	DIN DN 200						1079/1469		475	410	115/505		119.5/145.0	64/99
	DIN DN 100						1079/1469		475	304	221/661		121.5/147.0	65/100
	DIN DN 125						1169/1459		525	380	185/575		127.5/153.0	75/110
	DIN DN 150						1169/1559		525	365	200/590		133.5/159.0	75/110
520x/522x	DIN DN 200	600	-	380	406.4	510	1204/1594	244	525	365	235/625	420/810	140.5/166.0	83/118
	DIN DN 80						1144/1584		465	410	191/631		158.4/202.4	89/142
	DIN DN 100						1144/1584		465	304	297/737		160.4/204.4	90/143
	DIN DN 125						1256/1696		525	380	271/711		170.4/214.4	104/157
	DIN DN 150						1256/1696		525	365	286/726		175.4/219.4	106/159
400x/402x	DIN DN 200	600	-	330	355.6	460	1256/1696	266	525	365	236/676	420/810	179.4/223.4	110/162
	DIN DN 250						1324/1764		560	450	420/810		194.4/238.4	125/178
	DIN DN 80						1079/1469		475	410	115/505		119.5/145.0	64/99
	DIN DN 100						1079/1469		475	304	221/661		121.5/147.0	65/100
	DIN DN 125						1169/1459		525	380	185/575		127.5/153.0	75/110
780x/782x	DIN DN 150	740	-	480	508	620	1169/1559	255	525	365	200/590	500/940	133.5/159.0	75/110
	DIN DN 200						1204/1594		525	365	235/625		140.5/166.0	83/118
	DIN DN 250						1260/1700		540	304	336/776		225.6/282.6	161/246
	DIN DN 125						1260/1700		540	380	260/700		229.6/286.6	162/247
	DIN DN 150						1260/1700		540	365	275/715		234.6/291.6	163/248
1500x/1502x	DIN DN 200	1000	-	690	711	830	1380/1820	263	600	460	240/680	500/940	249.6/306.6	190/275
	DIN DN 250						1425/1865		600	450	250/690		259.6/316.6	194/279
	DIN DN 300						1495/1935		670	515	235/675		476.0/570.0	391/558
													488.0/582.0	397/564
													513.0/607.0	426/593

DIN flange connection to DIN EN ISO 1092-1, PN 16 (with sealing strip, flange shape B1)

NOTE

The information in this brochure relates to the operating conditions and applications described.

For applications or operating conditions not described, please contact the relevant technical department.

Subject to technical modifications.

HYDAC Filtrertechnik GmbH
Industriegebiet