▼ Shown from left to right: P25, P51, P18



- P25 and P50 pump oil in both forward and reverse handle movement improving overall efficiency, ideal when mounting space is restricted
- **External load-release valve**
- Internal pressure-relief valve for overload protection
- For use with single-acting cylinders and tools
- P18 vertical operation requires pump head facing down
- P25 and P50 vertical operation requires pump vent side facing down
- P51 for horizontal operation only.

## When Less Than 700 bar is All You Need



#### **GA45GC Gauge Adaptor**

Protect yourself from system overloading by simply ordering one part number for a pre-assembled gauge, adaptor block and coupler.





#### Hoses

Enerpac offers a complete line of high quality hydraulic hoses. To ensure the integrity of your system, specify only genuine Enerpac hydraulic hoses.

P18 hand pump used for locking the rotating table for marble polishing.



Pump Type	Usable Oil Capacity  (cm³)	Model Number *	Pressure Rating (bar)	Oil Displacement per Stroke (cm³)	Max. Handle Effort (kg)	
	360	P18	200	2,46	16	
	300	FIO	200	2,40	10	
Single-	3277	P25	175	9,50	27	
Speed	3277	P50	350	4,75	27	
	819	P51	200	4,10	27	

<sup>\*</sup> For use with single-acting cylinders and tools

# **Low Pressure Hand Pumps**

### P **Series**



Reservoir Capacity:


360 - 3277 cm<sup>3</sup>

Flow at Rated Pressure:

2,46 - 9,50 cm<sup>3</sup>/stroke


Maximum Operating Pressure:

175 - 350 bar



Н


P18




1/4"-18NPTF


E.

P25, P50



P51





**MP-Series Multifluid Hand Pumps** 

Corrosion resistant hand pumps for low pressure filling and high pressure testing applications, suitable for a wide range of fluids.

Page:

▼ P51 hand pumps used with RC-series cylinders to keep wooden layers under pressure during lamination of plates.



Piston Stroke	Dimensions (mm)												Model Number *
(mm)	Α	В	С	D	E	Н	J	L	М	N	S	(kg)	
25,4	221	316	30	35	37	385	254	163	_	140	8,4	5,0	P18
38,1	152	173	152	240	_	_	_	684	200	_	10	16,3	P25
38,1	152	173	152	240	-	-	-	684	200	_	10	16,8	P50
25,4	52	92	181	200	57	610	29	160	129	_	9	5,4	P51