


Digital
multi-axis NC control

RE 30156/03.12 1/16
Replaces: 04.05

Type VT-MAC8

Component series 1X



H 7304

Table of contents

Contents	Page
Features	2
System overview	2
Ordering code for system	3
Software project planning	4
Overview of the controller functions	4
NC interpreter	5
ECL-Win programming language	6
Technical data	7
Pin assignment master card	9
Pin assignment slave card	12
Unit dimensions	13

Features

The MAC8 is the digital Rexroth multi-axis NC control in modular design. It consists of a master card with no, 2 or 4 axis controllers and can be extended with up to seven slave cards for four axes each, if necessary. It is thus the perfect solution for complex control tasks with up to 32 interpolatable axes. Using local Ethernet, more MAC8 can be connected. The MAC8 communicates with the superior PLC machine control via field bus (PROFIBUS DP or CAN) or via Ethernet. It has special hydraulic control characteristics and is able to control the movements of the machine or machine parts in a completely automatic manner and can thus also accept PLC tasks. Sensors and actuators can also be analyzed and/or activated via CAN bus.

Areas of application:

- Presses (tube forming, metal / ceramic, powder, plastic, deep drawing, glass presses, press brakes, die cushion controls, IHF (internal high pressure forming, etc.))
- Materials handling (container crane, balance crane, train/truck lift, belt drive, etc.)
- Steelworks and rolling mill technology (continuous caster, curved casting machine, mold oscillation, roll stand, 3-roll bending machine, turn over cooling bed, flying shears, ladle car, molding plants, etc.)
- Testing technology (weld testing machine, shock absorber testing system, tube testing press, etc.)
- Special machinery (coal distributors, thick sheet turning equipment, engine turning system, etc.)

Process connection

32 digital inputs, 24 digital outputs, PROFIBUS DP, CANopen, TCP-IP, UDP, PROFINET RT, EtherNet/IP

Connection / visualization

- By means of "OPC server"
- By means of "Active X" elements
- Interfaces: RS485 or Ethernet

Programming

- User programming with PC
- Extensive diagnosis and debugging tools
- Comfortable data administration on the PC
- High level language oriented
- 32 NC programs which can be executed in parallel
- High execution speed due to compiled programs
- Fast integer and real arithmetics
- Exponential and angle functions


Hydraulic axes

- Measuring system Incremental or absolute (SSI)
Analog ± 10 V and 4 to 20 mA,
 ± 10 mA and ± 20 mA
- Control output Analog ± 10 V and 4 to 20 mA,
 ± 10 mA and ± 20 mA

Closed-loop control

- Following controller
- State controller
- Path-dependant braking
- Synchronization controller up to 32 axes (different variants)
- Pressure / force controller

System overview



Ordering code for system

VT-MAC 8-1X/ S				M	AX4	*
System with						Further details in the plain text
1 slot	= 1					4-axis slave
5 slots	= 5					Number
8 slots	= 8					Master
Bus variant					0 to 7 =	
No field bus	= A					without axis module, with RS485
PROFIBUS DP slave connection	= P				1 =	2-axis version, with RS485
PROFINET RT / EtherNET/IP slave connection	= E				2 =	4-axis version
					4 =	

Selection aid

Part Ordering code	Analog In	RS232 (V24) RS485	CANopen	PROFINET RT / EtherNet/IP	PROFIBUS DP	Analog I/O	Encoder plug
AM 1	X	X	X				
AM 2	X	X	X			X	2X
AM 4	X		X			X	4X
PM 1	X	X	X		X		
PM 2	X	X	X		X	X	2X
PM 4	X		X		X	X	4X
EM 4	X		X	X		X	4X

Components

Material no.	Type	Designation
R901075726	VT-MAC8-1X/K-AM1	Master card without axis controller
R901075728	VT-MAC8-1X/K-AM2	Master card with 2 axis controllers
R901075730	VT-MAC8-1X/K-AM4	Master card with 4 axis controllers
R901075732	VT-MAC8-1X/K-PM1	Master card with PROFIBUS DP, without axis controller
R901075734	VT-MAC8-1X/K-PM2	Master card with PROFIBUS DP, with 2 axis controllers
R901075738	VT-MAC8-1X/K-PM4	Master card with PROFIBUS DP, with 4 axis controllers
R901275171	VT-MAC8-1X/K-EM4	Master card with PROFIBUS RT / EtherNet/IP, with 4 axis controllers
R901075752	VT-MAC8-1X/K-AX4	Slave card with 4 axis controllers
R901075757	VT-MAC8-1X/K-DUMMY	Blank location cover for a slot
R901075714	VT-MAC8-1X/K-RACK1	Empty rack with one slot (master card)
R901075722	VT-MAC8-1X/K-RACK5	Empty rack with 5 slots (1 master, 4 slaves)
R901075725	VT-MAC8-1X/K-RACK8	Empty rack with 8 slots (1 master, 7 slaves)
R901052075	KABELSATZ MAC8/ABS/SF/3M	Cable absolute value encoder SSI (X2), 3 meters, open end
R901052153	KABELSATZ MAC8/INC/24V/SF3M	Cable incremental encoder 24V (X2), 3 meters, open end
R901052152	KABELSATZ MAC8/INC/5V/SF/3M	Cable incremental encoder 5V (X2), 3 meters, open end
R901052141	KABELSATZ MAC8/AE/SF/3M	Cable analog inputs (X4), 3 meters, open end
R901052069	KABELSATZ MAC8/AEA/SF/3M	Cable analog inputs/outputs (X1), 3 meters, open end
R901052150	KABELSATZ MAC8/DEA/SF/3M	Cable digital inputs/outputs (X5), 3 meters, open end
R901074828	KABELSATZ MAC8/PC/RS232/5M	Cable PC MAC8 RS232 interface (X3.4), 5 meters
R901269556	SYS-MAC8-2X-D/E	Installation CD for the MAC8 programming system

Software project planning

Program creation with MACpro

- Windows version with integrated editor with command highlighting
- Project group creation for managing the individual programs on the slots with automatic switch-over
- Global header files for joint definitions
- Programs can be organized in modules (files)
- Nesting depth for up to 50 subroutines
- Change-oriented compiling and transmission to the MAC8
- Reference list of the variables and subroutines used
- Automatic version comparison PC <-> MAC8
- Saving of different desktop settings
- Program stored in the flash

Debugging

- Online help for "Syntax", "Tools" and "Keys"
- Tracing of program execution (Trace)
- Process variable tracing by means of trend
- Program view (View) with search functions
- Function level display (call hierarchy)
- 5 break points are managed
- Stop / start / continue and single step (single, step, step-over) of individual or all programs
- Saving of the memory image (program with data)

View of variables

- All variable windows can be selected by means of "Hot keys" or the menu, flexible window size
- Configurable variable window (mix variables) with hexadecimal, decimal, binary and floating point representation. Easy transmission of any variable from the program view to the tracing window and structuring by means of comments
- Setup window with all axis-specific process variables
- System parameter assistant

Acquisition of measured data

- 64 recording channels with start and stop trigger
- Recording option for all process variables
- Graphical and numeric presentation (DBF format) of the recorded channels
- Endless data recording (trend)

Commissioning functions

- Inputs can be simulated
- Outputs can be set
- Analog output variables can be set
- Jog mode for controller optimization
- Activation / deactivation of individual controller components

Project-related management of the:

- Programs
- Configurable programming user interface
- System parameters
- Measured data

MACpro system requirements:

- IBM PC or compatible system
- Windows NT, Windows 2000, Win XP, Windows 7
- Processor from 300 MHz
- At least 256 MB RAM
- At least 100 MB of available hard disk capacity

The installation is effected from CD
(SYS-MAC8-2X-D/E with material no. **R901269556**)

Overview of the controller functions

Position controller:

- Following controller
- Substitutional closed-loop control (position / pressure)
- Force limitation in positive and negative direction
- Direction-dependent gain adjustment
- "Inflected" gain characteristic curve
- Fine positioning
- Residual voltage principle
- Compensation of zero point errors
- State feedback
- Command value feedforward
- Limitation of the control output via the NC program

- "Path-dependant braking"
- External controller function via NC program
- Following operation
- Velocity override
- Gain modification via the NC program possible
- Interpolation of up to 32 axes
- Pre-acceleration
- Force / path; force / time curves
- Position/ input value curves
- Coordinate transformation of the spatial axes

Overview of the controller functions (continued)

State controller:

- Velocity feedback
- Acceleration feedback
- Pressure feedback
- External feedback

Pressure / force controller:

- PID controller
- I share can be switched via window
- Differential pressure evaluation
- P / Q pilot control
- Different modes for transition from position to force controller

Velocity controller:

- PI controller
- I share switchable via window

Synchronization controller:

- Synchronization of any groups with up to 32 axes, which can be changed during runtime
- Active synchronization with force limitation and/or parallel making way
- Passive synchronization, tilt compensation control, with definable average counterforce
- Synchronization offsets of the axes can be changed dynamically
- Axes can be dynamically added to or removed from the synchronized group (also during operation)
- Relative synchronization, also in opposite direction


Monitoring functions:

- Dynamic following error monitoring
- Traversing range limits (electronic end switches)
- Cable break monitoring for incremental and SSI encoder
- Cable break monitoring for sensors with output 4 to 20 mA
- Valve monitoring
- Encoder voltage monitoring

NC interpreter

The NC interpreter organizes the execution of the 32 parallel NC programs. In this connection, each program works in a sequential manner. Switch-over between the parallel programs is in each case effected after processing of one program line. In case of commands waiting for an event (e.g.: "WAIT", "POS"), the next program is activated immediately after the event request in order not to hinder execution of the

other programs. All system resources are available for all programs (I/O, axes, variables etc.). Programs can start, stop or delay each other. This concept allows for the perfect imaging of the sequence control of the machine in the NC program of the MAC8.



ECL-Win programming language

The MAC8 data organization: Numeric variables (integer): V: Standard variables P: Local variables N: Process variables Fields (integer): A: User defined fields S: System parameters Real variables: R: Floating point figures Logic variables: I: Inputs O: Outputs F: Process flags	Program sequence control: IF ELSE Instruction WHILE Loop {..} Command block [..] Bundling of commands BEGIN END Program definition Label JUMP <Label> or <Subroutine> START/STOP/BREAK/CONT<Program> WAIT <Time> or <Condition>
Signs and operators: <num. signs> {"-" "!" "#"} <num. operator> {"*" "/" "+" "-" "&" " " "^" "<<" ">>"} <num. real operator> {"sin" "cos" "tan" "asin" "acos" "atan" "sqrt"} <log. operator> {"&" " " "^"} <num. comp.operator> {"<=" ">=" "<" ">" "="}	Data manipulation: DIM Field declaration COPY Field copying function SET Assign variable MSET Preset fields PSET Assign local variable
Compiler instructions: "," <Comment> "#include" <File name> "#module" <File name> "#define" <Name> <Text> "#global" <File name>	Axis/process functions: AXINIT Initialize axes AXSET Take over axis data STOP Cancel axis movement HALT Immediate halt of axis movement POS HALT Immediate halt of axis movement BREAK Interrupt axis movement CONT Resume axis movement EQUIT Acknowledge axis error LOCK Lock axis control UNLOCK Unlock control OVER Determine axis override ACC Axis acceleration ($\pm$) VEL Axis velocity POS Position axis SYNCH Define synchronized axes LIN Linear interpolation FORCE Force control DAC Voltage output FUNC Axis functions SIMU Simulation of axis HOME Referencing TABLE Process curve creation VIRTUAL Define virtual axes REAL Inverse calculation formula for VIRTUAL FREEZE Freeze axis velocity
Acquisition of measured values: TIMER Timer TRACE Oscilloscope function	For the operating parameters not listed here, you can usually enter a constant, a variable or a term!
Dialog command (control box or terminal): DIALOG Start dialog WINDOW Define window DISPLAY Output variable or text INPUT Input definition LEVEL User level READ_KEY Softkey query SSET String assignment	
Special commands: CALL <Address> Call C function START/STOP TASK Start C task	

Technical data

Operating voltage	U_B	18 to 36 VDC / max 3.6 A
Current consumption	Master without axis	500 mA
	Master with axes	800 mA
	Slave	400 mA
Processor		MPC860 and MPC555
Memory		16 MB SDRAM, 16 MB Flash, 8 KByte DPR 4 MB Flash (MPC555) 2 MB SRAM (MPC555)
Analog inputs:		
– Voltage inputs (differential inputs)		
• Input voltage	U_E	± 10 V, 12 bits with 4-fold oversampling
• Input resistance	R_E	Max. +10 V to –10 V 160 k Ω
• Resolution		5 mV
– Current inputs		
• Input current / input resistance	I_E / R_E	4 to 20 mA / 100 Ω ± 20 mA / 500 Ω
• Leakage current	I_V	12 μ A
• Resolution		4 μ A
Analog outputs:		
– Voltage outputs		
• Output voltage	U_{nom}	± 10 V PWM (pulse width modulation)
• Output current	I_{max}	10 mA
• Load	R_{min}	2 k Ω
– Current outputs		
• Output current normalized	I_{nom}	± 20 mA
• Load	R_{max}	500 Ω
• Resolution		1 mV
Serial interfaces	Standard	RS232 (V 24) (19.2 KBaud) RS485 (115 KBaud)
	Optional	PROFIBUS DP (max. 12 MBaud) CANopen (max. 1 MBaud)
Switching inputs	Quantity	32
	Logic level	log 0 (low) 0 V to +5 V log 1 (high) +10 V to 36 V
	R_E	3 k Ω ± 10 %
Switching outputs	Quantity	24
	Logic level	log 0 (low) 0 V to +5 V; log 1 (high) +10 V to 36 V; current carrying capacity up to 50 mA

Technical data (continued)

Digital position transducers		
– Incremental transducer		
• Transducer with TTL output		
Input voltage	log 0	0 to 1 V
	log 1	2.8 to 5.5 V
Input current	log 0	–0.8 mA (with 0 V)
	log 1	0.8 mA (with 5 V)
Max. frequency referring to Ua 1	$f_{\max}$	250 kHz, 24 bit
SSI position transducers		
– Coding		
Gray-Code		
– Data width		
Adjustable up to max. 28 bit		
– Line receiver (TTL)	$f_{\max}$	250 kHz
– Input voltage	log 0	0 to 1 V
	log 1	2.5 to 5.5 V
– Input current	log 0	–0.5 mA (with 0 V)
	log 1	0.5 mA (with 5 V)
– Line driver		
– Output voltage		
	log 0	0 to 0.5 V
	log 1	2.5 to 5.5 V
Admissible operating temperature range		0 to 50 °C
Storage temperature range		–20 to 70 °C
Weight:		
– Rack 1	<i>m</i>	1000 g
– Rack 5	<i>m</i>	1800 g
– Rack 8	<i>m</i>	2500 g
– Master card	<i>m</i>	400 g
– Slave card	<i>m</i>	350 g
– Blank cover	<i>m</i>	100 g

Pin assignment master card VT-MAC8


Front plate shows: VT-MAC8-1X/K-PM1

X1a RJ-45; 100BaseT Ethernet	
Pin	
1	TPO+
2	TPO-
3	TPI+
4	75K-GND
5	75K-GND
6	TPI-
7	75K-GND
8	75K-GND

X1b RJ-45; 10BaseT Ethernet	
Pin	
1	TPO+
2	TPO-
3	TPI+
4	n.c.
5	n.c.
6	TPI-
7	n.c.
8	n.c.

X4 Analog in		
Pin		Pin
1	U_{in1C}	
	U_{in2C}	6
2	U_{in3C}	
	U_{in4C}	7
3	AGND	
	U_{in1D}	8
4	U_{in2D}	
	U_{in3D}	9
5	U_{in4D}	

X6 Voltage supply	
Pin	
1	Shield
2	GND
3	+24 V



X3.1 CANopen		
Pin		Pin
1	n.c.	
	n.c.	6
2	CAN_Lx	
	CAN_Hx	7
3	GND CANx	
	n.c.	8
4	n.c.	
	n.c.	9
5	n.c.	


X3.3 PROFIBUS DP		
Pin		Pin
1	n.c.	
	VP	6
2	n.c.	
	n.c.	7
3	RxD/TxD -P	
	RxD/TxD -N	8
4	CNTR -P	
	n.c.	9
5	DGND	

Notice:
Please use straight
Profibus connector

X3.4 RS232 (V24)		
Pin		Pin
1	GND	
	RxD	6
2	TxD	
RS485		
	GND	7
3	5 V	
	RxD+	8
4	RxD-	
	TxD+	9
5	TxD-	

Pin assignment master card VT-MAC8

Front plate shows: VT-MAC8-1X/K-PM2




X5		Digital I/O			
Pin	Description	Pin	Description	Pin	Description
		22	Reserved		
43	Reserved			1	Reserved
		23	In0	2	In1
44	In2			3	In4
		24	In3	4	In7
45	In5			5	In10
		25	In6	6	In13
46	In8			7	In16
		26	In9	8	In19
47	In11			9	In22
		27	In12	10	In25
48	In14			11	In28
		28	In15	12	In31
49	In17			13	Out2
		29	In18	14	Out5
50	In20			15	Out8
		30	In21	16	Out11
51	In23			17	Out14
		31	In24	18	Out17
52	In26			19	Out20
		32	In27	20	Out23
53	In29			21	0 V
		33	In30		
54	Out0				
		34	Out1		
55	Out3				
		35	Out4		
56	Out6				
		36	Out7		
57	Out9				
		37	Out10		
58	Out12				
		38	Out13		
59	Out15				
		39	Out16		
60	Out18				
		40	Out19		
61	Out21				
		41	Out22		
62	0 V				
		42	0 V		

Notice:

The pins marked with "reserved" must not be connected.

Pin assignment master card VT-MAC8

Front plate shows: VT-MAC8-1X/K-EM4



X1 Analog I/O on master card			
Pin		Pin	Description
1	n.c.		
	n.c.	14	
2	AGND		Analog ground
	n.c.	15	
3	n.c.		
	AGND	16	Analog ground
4	IU _{in} 1 _A		Current / voltage input 0.. 20 mA / ±10 V
	IU _{in} 1 _B	17	Current / voltage input 0.. 20 mA / ±10 V
5	IU _{in} 2 _A		Current / voltage input 0.. 20 mA / ±10 V
	IU _{in} 2 _B	18	Current / voltage input 0.. 20 mA / ±10 V
6	AGND		Analog ground
	IU _{in} 3 _A	19	Current / voltage input 0.. 20 mA / ±10 V
7	IU _{in} 3 _B		Current / voltage input 0.. 20 mA / ±10 V
	IU _{in} 4 _A	20	Current / voltage input 0.. 20 mA / ±10 V
8	IU _{in} 4 _B		Current / voltage input 0.. 20 mA / ±10 V
	AGND	21	Analog ground
9	U _{out} 1		±10 V
	U _{out} 2	22	±10 V
10	U _{out} 3		±10 V
	U _{out} 4	23	±10 V
11	AGND		Analog ground
	I _{out} 1	24	±20 mA
12	I _{out} 2		±20 mA
	I _{out} 3	25	±20 mA
13	I _{out} 4		±20 mA


X2.x Encoder plug		
Pin	INC	SSI
1	/Ua 2	
2		+Clk
3	Ua 0	
4	/ Ua 0	
5	Ua 1	
6	/ Ua 1	
7		-Clk
8	Ua 2	
9		-Data
10	0 V	0 V
11		+Data
12	Reserved	Reserved
13	n. c.	n. c.
14	Reserved	Reserved
15	n. c.	n. c.

X3.3 PROFINET RT / EtherNet/IP	
Pin	
1	TPO+
2	TPI+
3	TPO-
4	TPI-

Notice:

The pins marked with "reserved" must not be connected.

Pin assignment slave card VT-MAC8-1X/K-AX4



X1 Analog I/O on slave card			
Pin		Pin	Description
1	I_{in1C}		Current / voltage input ± 20 mA / ± 10 V
	I_{in2C}	14	Current / voltage input ± 20 mA / ± 10 V
2	AGND		Analog ground
	I_{in3C}	15	Current / voltage input ± 20 mA / ± 10 V
3	I_{in4C}		Current / voltage input ± 20 mA / ± 10 V
	AGND	16	Analog ground
4	IU_{in1A}		Current / voltage input 0...20 mA / ± 10 V
	IU_{in1B}	17	Current / voltage input 0...20 mA / ± 10 V
5	IU_{in2A}		Current / voltage input 0...20 mA / ± 10 V
	IU_{in2B}	18	Current / voltage input 0...20 mA / ± 10 V
6	AGND		Analog ground
	IU_{in3A}	19	Current / voltage input 0...20 mA / ± 10 V
7	IU_{in3B}		Current / voltage input 0...20 mA / ± 10 V
	IU_{in4A}	20	Current / voltage input 0...20 mA / ± 10 V
8	IU_{in4B}		Current / voltage input 0...20 mA / ± 10 V
	AGND	21	Analog ground
9	U_{out1}		± 10 V
	U_{out2}	22	± 10 V
10	U_{out3}		± 10 V
	U_{out4}	23	± 10 V
11	AGND		Analog ground
	I_{out1}	24	± 20 mA
12	I_{out2}		± 20 mA
	I_{out3}	25	± 20 mA
13	I_{out4}		± 20 mA

X2.x Encoder plug		
Pin	INC	SSI
1	/Ua 2	
2		+Clk
3	Ua 0	
4	/ Ua 0	
5	Ua 1	
6	/ Ua 1	
7		-Clk
8	Ua 2	
9		-Data
10	0 V	0 V
11		+Data
12	Reserved	Reserved
13	n. c.	n. c.
14	Reserved	Reserved
15	n. c.	n. c.

S1	Address
	Slot
2	Slot 2
3	Slot 3
4	Slot 4
5	Slot 5
6	Slot 6
7	Slot 7
8	Slot 8
0 - 1	Not allowed
9 - F	Not allowed

Notice:

Address the card according to the slot.


Notice:

The pins marked with "reserved" must not be connected.

Unit dimensions (dimensions in mm)


VT-MAC8-1X/K-RACK5

System with 5 slots



VT-MAC8-1X/K-RACK1


System with 1 slot



Unit dimensions (dimensions in mm)

VT-MAC8-1X/K-RACK8

System with 8 slots



Unit dimensions (dimensions in mm)

VT-MAC8-1X/K-RACK1/5/8

